

# Upside/down drillstand DST200KF

## Product description

- Guaranteed waterproof ceiling- and floordrilling
- Very quick installation from drillstand including watercollection
- Little drilldistance from wall (even with small diameters)
- For drilling up to diameter 250mm
- Maximum drilllength 1200mm
- Extendable for horizontal drilling without anchoring
- Anchors unnecessary
- 100% watercollection by using seals
- Seal supply stability at drilling
- With special foot very suitable for serial drilling

## Spare parts

Position	Order No.	Designation
2	150.1.0KF.KF	Support complete (painted)
201	FS.1700.50	Outside column 1700 mm 50x50 stainless steel
202	11E.03.205	Inside column 1700 mm 40x40 galv.
203	11E.03.215.K4	Fine adjustment 40x40 complete
204	880.03.252.0044	Gas pressure spring 08-19
205	508.9	Polyamide plate Ø 100
205	508.5	Polyamide plate Ø 120
206	508.6	Spindel galv. M16 x 125
207	505.02.516	Shell 3.V50 x 2.5 / M16
208	564.10.140.6000	Wheel Ø 100x25GL
209	464.10.140.6000	Wheel Ø 100x24GL
210	150.1.18.KFK-H	Rapid switch plate special construction for horizontal drilling
	600.1.19.K	Rapid switch plate complete
	600.1.18.KF.K	Rapid switch plate
	1114051	Foot for upside/down drillstandard incl. wheels Ø 100 and gas pressure springs
211	1105050	Adapter stainless steel 50x50